

Model FR Clear File Number: R40252

COMPANY

FLAMEOFF COATINGS INC
3915 Beryl Rd. Suite 130
RALEIGH, NC 27607 United States

MODEL INFO

FR Clear

SURFACE BURNING CHARACTERISTICS - U.S.

Coating Type	Number of Coats	Rate Per Coat, ft ² /gal	Flash Point (Closed Cup), °F	Substrate Applied To	Flame Spread Index	Smoke Developed Index
Fire Retardant Coats	1	300	No Flash to Boiling	Red Oak	25	200



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."